



PNEUMATIC TRAILERS

SPECIFICATIONS:

- 1040 CUBIC FOOT CAPACITY
- 3-HOPPER, 45°
- CONSTRUCTION
- ALUMINUM END FRAMES
- ALUMINUM STRUTS
- SILENT DRIVE SUSPENSION
- "HP" (PARALLEL SPINDLE)
- DURA-LIGHT HUBS, CENTRIFUSE BRAKE DRUMS
- STEMCO PPS WHEEL ENDS (5-YR/500,000-MILE WARRANTY)
- STEEL AIR TANK
- ALUMINUM MACHINE FINISH WHEELS
- 11R22.5 14-PLY TIRES, ALUMINUM WHEELS (OUTSIDE ONLY)
- POWDER COATED 2 SPEED LANDING GEAR
- 5" ULTRAFLO #400 PRODUCT VALVES
- 5" X 4" ALUMINUM STRAIGHT TEES
- REAR DISCHARGE UNDER HUMP AXLESSOLIMAR AERATION W/STAINLESS STEEL HOPPER SAVERS
- LED LIGHTS W/SEALED WIRING HARNESS
- HIGH MOUNTED 3RD STOP LIGHT
- TRAILER WEIGHT: PENDING OPTIONS
- 4" STEEL PIPING
- 3" UCT AIR LINE
- ALL PIPES ON DRIVERS SIDE
- 3 MANWAYS, 20" CAMLOCK
- PRESSURE RELIEF VALVE ON TOP
- GAGE BOX ON DRIVERS SIDE
- 3" CHECK VALVE FROM FRONT OF TRAILER TO TOP AIRLINE
- LIGHT ABOVE PRESSURE GAUGE
- 3 HOSE CONTAINERS PER SIDE/ 1 – 20', 2 – 10' PER SIDE
- 3" AERATOR LINES WITH 2" HOSE RUNNING TO HOPPERS
- FIXED TANDEM AXLE/HUMP AXLE
- OVERALL LENGTH OF TRAILER WILL BE 42 FEET 3 INCHES
- OVERALL HEIGHT OF TRAILER WILL BE 12 FEET
- OVERALL WIDTH OF TRAILER WILL BE 96 INCHES