

PRO-SET® INF-210 Hardener**Safety Data Sheet**

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Date of issue: 06/01/2015

Revision date: 10/06/2016

Version: INF-210-2016a

SECTION 1: Identification**Identification**

Product form : Mixtures
Product name : PRO-SET® INF-210 Hardener
Product code : INF-210, INF-210-1, INF-210-2, INF-210-3, INF-210-4, INF-210-5, INF-210-6

Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Curing agent for epoxy resins

Details of the supplier of the safety data sheet**Manufacturer**

Gougeon Brothers, Inc
 100 Patterson Ave.
 Bay City, MI 48706 - U.S.A.
 T 888-377-6738 or 989-684-7286
www.prosetepoxy.com

Emergency telephone number

Emergency number : CHEMTREC 1 (800) 424-9300
 CHEMTREC International +1 (703) 527-3887 24 hr

SECTION 2: Hazard(s) identification**Classification of the substance or mixture**

Acute Tox. 4 (Oral)
 Acute Tox. 4 (Dermal)
 Acute Tox. 4 (Inhalation)
 Skin Corr. 1B
 Eye Dam. 1
 Skin Sens. 1
 Repr. 2
 STOT SE 3
 Aquatic Acute 3
 Aquatic Chronic 3

Label elements**Hazard pictograms (GHS)****Signal word (GHS)**

Danger

Hazard statements (GHS)

Harmful if swallowed, in contact with skin or if inhaled. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause respiratory irritation. Suspected of damaging fertility or the unborn child. Harmful to aquatic life. Harmful to aquatic life with long lasting effects

Precautionary statements (GHS)

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust, fume, gas, mist, vapours, spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves, protective clothing, eye protection, face protection. If swallowed: rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Immediately call a poison center/doctor. If skin irritation or rash occurs: Get medical attention/advice. Take off contaminated clothing and wash it before reuse. Collect spillage. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

PRO-SET® INF-210 Hardener

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Other hazards

No additional information available

Unknown acute toxicity

No additional information available

SECTION 3: Composition/information on ingredients

Substance

Not applicable

Mixtures

| Name | Product identifier | % |
|--------------------------------------|---------------------|---------|
| 1,5-Pentanediamine, 2-methyl- | (CAS No) 15520-10-2 | 30 - 50 |
| 4-tert-Butylphenol | (CAS No) 98-54-4 | 10 - 30 |
| Isophorone diamine | (CAS No) 2855-13-2 | 10 - 20 |
| 1,3-Benzenedimethanamine | (CAS No) 1477-55-0 | 5 - 15 |
| 1,3-Cyclohexanedimethanamine | (CAS No) 2579-20-6 | 5 - 15 |
| 2,4,6-Tri(dimethylaminomethyl)phenol | (CAS No) 90-72-2 | 1 - 10 |

The exact chemical identity and/or exact percentage (concentration) of each ingredient may be held as confidential business information (CBI). Any ingredient not disclosed in this section may have been determined not to be hazardous to health or the environment, or it may be present at a level below its disclosure threshold. Refer to Section 15 for additional information regarding this CBI claim.

SECTION 4: First aid measures

Description of first aid measures

First-aid measures after inhalation

: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Immediately call a POISON CENTER or doctor/physician.

First-aid measures after skin contact

: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or doctor/physician.

First-aid measures after eye contact

: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.

First-aid measures after ingestion

: Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician. Rinse mouth.

Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation

: Harmful if inhaled. May cause respiratory irritation.

Symptoms/injuries after skin contact

: Harmful in contact with skin. Causes severe burns. Symptoms may include redness, pain, blisters. Repeated exposure to this material can result in absorption through skin causing significant health hazard. May cause an allergic skin reaction.

Symptoms/injuries after eye contact

: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.

Symptoms/injuries after ingestion

: Harmful if swallowed. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. May cause stomach distress, nausea or vomiting.

Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media

: Foam. Carbon dioxide. Dry chemical. Water spray.

Unsuitable extinguishing media

: Do not use a heavy water stream.

Special hazards arising from the substance or mixture

Fire hazard

: Products of combustion may include, and are not limited to: oxides of carbon, nitrogen oxides, amines, ammonia, nitric acid, cyanides, aldehydes, nitrosamines. When mixed with sawdust, wood chips, or other cellulosic material, spontaneous combustion can occur under certain conditions. Heat is generated as the air oxidizes the amine. If the heat is not dissipated quickly enough, it can ignite the sawdust.

Reactivity

: No dangerous reaction known under conditions of normal use.

PRO-SET® INF-210 Hardener

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Advice for firefighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

For non-emergency personnel

No additional information available

For emergency responders

No additional information available

Environmental precautions

Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE). Do not absorb in sawdust, paper, cloth or other combustible absorbents.

Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Do not breathe dust, fume, gas, mist, vapours, spray. Do not swallow. Handle and open container with care. Use only outdoors or in a well-ventilated area. Do not eat, drink or smoke when using this product. Use personal protective equipment as required. When mixed with epoxy resin this product causes an exothermic reaction, which in large masses, can produce enough heat to damage or ignite surrounding materials and emit fumes and vapors that vary widely in composition and toxicity.

Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Keep only in the original container in a cool, well-ventilated place. Protect from moisture. Storage temperature : 40°F (4°C) - 90°F (32°C).

SECTION 8: Exposure controls/personal protection

Control parameters

| | | |
|---------------------------------------------------|------------------------------------------|-----------------------|
| 1,5-Pentanediamine, 2-methyl- (15520-10-2) | | |
| Not applicable | | |
| 4-tert-Butylphenol (98-54-4) | | |
| Not applicable | | |
| Isophorone diamine (2855-13-2) | | |
| Not applicable | | |
| 1,3-Benzenedimethanamine (1477-55-0) | | |
| ACGIH | ACGIH Ceiling (mg/m ³) | 0.1 mg/m ³ |
| NIOSH | NIOSH REL (ceiling) (mg/m ³) | 0.1 mg/m ³ |
| 1,3-Cyclohexanedimethanamine (2579-20-6) | | |
| Not applicable | | |

PRO-SET® INF-210 Hardener

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

2,4,6-Tri(dimethylaminomethyl)phenol (90-72-2)

Not applicable

Exposure controls

- Appropriate engineering controls** : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
- Hand protection** : Wear chemically resistant protective gloves.
- Eye protection** : Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and face protection (face shield).
- Skin and body protection** : Wear suitable protective clothing.
- Respiratory protection** : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Environmental exposure controls** : Maintain levels below Community environmental protection thresholds.
- Other information** : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

- Physical state** : Liquid
- Appearance** : No data available
- Colour** : Colourless
- Odour** : Ammonia
- Odour threshold** : No data available
- pH** : No data available
- pH solution** : 11.4
- Melting point** : No data available
- Freezing point** : No data available
- Boiling point** : > 400 °F (204°C) (estimated based on similar product)
- Flash point** : > 181 °F (82.8°C) (estimated based similar product)
- Relative evaporation rate (butylacetate=1)** : No data available
- Flammability (solid, gas)** : Not flammable
- Vapour pressure** : < 1 mm Hg @ 20°C / 68°F (estimated based on ingredient data)
- Relative vapour density at 20 °C** : No data available
- Relative density** : 0.94
- Solubility** : Appreciable.
- Partition coefficient n-octanol/water** : No data available
- Auto-ignition temperature** : No data available
- Decomposition temperature** : No data available
- Viscosity, kinematic** : 17 mm²/s @ 20°C / 68°F
- Viscosity, dynamic** : No data available
- Explosive limits** : No data available
- Explosive properties** : No data available
- Oxidising properties** : No data available
- Other information**
- VOC content** : 5.89 g/l (0.05 lb/gal)
- Bulk density** : 7.82 lb/gal (0.94 kg/L)

SECTION 10: Stability and reactivity

- Reactivity** : No dangerous reaction known under conditions of normal use.
- Chemical stability** : Stable under normal storage conditions.
- Possibility of hazardous reactions** : No dangerous reaction known under conditions of normal use. A mass of more than one pound of product plus an epoxy resin will cause irreversible polymerization with significant heat buildup and pressure.

PRO-SET® INF-210 Hardener

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| | |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Conditions to avoid | : Heat. Incompatible materials. |
| Incompatible materials | : Acids. Oxidizing materials. Halogenated compounds. |
| Hazardous decomposition products | : May include, and are not limited to: oxides of carbon, nitrogen oxides, amines, ammonia, nitric acid, cyanides, aldehydes, nitrosamines, phenolics. |

SECTION 11: Toxicological information

Information on toxicological effects

| 1,5-Pentanediamine, 2-methyl- (15520-10-2) | |
|---------------------------------------------------|-------------|
| LD50 oral rat | 1170 mg/kg |
| LD50 dermal rabbit | 1870 mg/kg |
| LC50 inhalation rat | 4.9 mg/l 1h |

| 4-tert-Butylphenol (98-54-4) | |
|-------------------------------------|-----------------------------------------------------------------------------------|
| LD50 oral rat | > 2000 mg/kg |
| LD50 dermal rat | No data. Intraperitoneal – mouse – 78 mg/kg. |
| LC50 inhalation rat | 5.6 mg/l Remarks: Nutritional and Metabolic: Weight loss or decreased weight gain |

| Isophorone diamine (2855-13-2) | |
|---------------------------------------|----------------|
| LD50 oral rat | 1030 mg/kg |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 inhalation rat | > 5.01 mg/l/4h |

| 1,3-Benzenedimethanamine (1477-55-0) | |
|---------------------------------------------|--------------|
| LD50 oral rat | 980 mg/kg |
| LD50 dermal rabbit | 2000 mg/kg |
| LC50 inhalation rat | 1.34 mg/l/4h |

| 1,3-Cyclohexanedimethanamine (2579-20-6) | |
|-------------------------------------------------|-----------------|
| LD50 oral rat | 700 - 780 mg/kg |
| LD50 dermal rabbit | 1700 mg/kg |

| 2,4,6-Tri(dimethylaminomethyl)phenol (90-72-2) | |
|-------------------------------------------------------|------------|
| LD50 oral rat | 2169 mg/kg |

| | |
|------------------------------------------|--------------------------------------------------------|
| Acute toxicity (oral) | : Oral: Harmful if swallowed. |
| Acute toxicity (dermal) | : Dermal: Harmful in contact with skin. |
| Acute toxicity (inhalation) | : Inhalation: Harmful if inhaled. |
| Skin corrosion/irritation | : Causes severe skin burns |
| Serious eye damage/irritation | : Causes serious eye damage. |
| Respiratory or skin sensitization | : May cause an allergic skin reaction. |
| Germ cell mutagenicity | : Not classified. |
| Carcinogenicity | : Not classified. |
| Reproductive toxicity | : Suspected of damaging fertility or the unborn child. |
| STOT-single exposure | : May cause respiratory irritation. |
| STOT-repeated exposure | : Not classified. |
| Aspiration hazard | : Not classified. |

| PRO-SET® INF-210 Hardener | |
|-------------------------------------------------|-----------------------|
| Viscosity, kinematic (calculated value) (20 °C) | 17 mm ² /s |

| | |
|------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Potential adverse human health effects and symptoms | : Harmful in contact with skin. Harmful if inhaled. Harmful if swallowed. |
| Symptoms/injuries after inhalation | : Harmful if inhaled. May cause respiratory irritation. |
| Symptoms/injuries after skin contact | : Harmful in contact with skin. Causes severe burns. Symptoms may include redness, pain, blisters. Repeated exposure to this material can result in absorption through skin causing significant health hazard. May cause an allergic skin reaction. |
| Symptoms/injuries after eye contact | : Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns. |

PRO-SET® INF-210 Hardener

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

- Symptoms/injuries after ingestion** : Harmful if swallowed. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. May cause stomach distress, nausea or vomiting.
- Other information** : Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

Toxicity

- Ecology - general** : Harmful to aquatic life with long lasting effects.

| 4-tert-Butylphenol (98-54-4) | |
|------------------------------|--------------------------------------------------------------------------------------|
| LC50 fish 1 | 4.71 - 5.62 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| EC50 Daphnia 1 | 3.9 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| LC50 fish 2 | 6.9 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static]) |
| EC50 Daphnia 2 | 3.4 - 4.5 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) |

| Isophorone diamine (2855-13-2) | |
|--------------------------------|-------------------------------------------------------------------------------|
| EC50 Daphnia 1 | 14.6 - 21.5 mg/l (Exposure time: 48 h - Species: Daphnia magna [semi-static]) |

Persistence and degradability

| PRO-SET® INF-210 Hardener | |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |

Bioaccumulative potential

| PRO-SET® INF-210 Hardener | |
|---------------------------|------------------|
| Bioaccumulative potential | Not established. |

| 4-tert-Butylphenol (98-54-4) | |
|---------------------------------------|----------|
| BCF fish 1 | 34 - 240 |
| Partition coefficient n-octanol/water | 2.44 |

| Isophorone diamine (2855-13-2) | |
|---------------------------------------|-----------------|
| Partition coefficient n-octanol/water | 0.79 (at 23 °C) |

Mobility in soil

| PRO-SET® INF-210 Hardener | |
|---------------------------|--------------------------------------|
| Ecology - soil | No additional information available. |

Other adverse effects

- Effect on the global warming** : No known effects from this product.

| Ingredient | CAS# | Ecotoxicity Classification Information |
|--------------------------------------|------------|----------------------------------------------|
| 1,5-Pentanediamine, 2-methyl- | 15520-10-2 | Not classified |
| 4-tert-Butylphenol | 98-54-4 | Acute Aquatic Cat. 2; Chronic Aquatic Cat. 2 |
| Isophorone diamine | 2855-13-2 | Chronic Aquatic Cat. 3 |
| 1,3-Benzenedimethanamine | 1477-55-0 | Acute Aquatic Cat. 3; Chronic Aquatic Cat. 3 |
| 1,3-Cyclohexanedimethanamine | 2579-20-6 | Acute Aquatic 3; Chronic Aquatic Cat. 3 |
| 2,4,6-Tri(dimethylaminomethyl)phenol | 90-72-2 | Acute Aquatic 3; Chronic Aquatic Cat. 3 |

- Other information** : Avoid release to the environment.

SECTION 13: Disposal considerations

Waste treatment methods

- Product/Packaging disposal recommendations** : Avoid release to the environment. This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

SECTION 14: Transport information

Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

In accordance with DOT and TDG

- UN-No. (DOT/TDG) : UN2735
- Proper Shipping Name (DOT/TDG) : Polyamines, liquid, corrosive, n.o.s. (1,5-Pentanediamine, 2-methyl-)

PRO-SET® INF-210 Hardener

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Class (DOT/TDG) : 8
Packing group (DOT/TDG) : II
Marine Pollutant : No

Transport by sea

In accordance with IMDG

UN-No. (IMDG) : 2735
Proper Shipping Name (IMDG) : POLYAMINES, LIQUID, CORROSIVE, N.O.S. (1,5-Pentanediamine, 2-methyl-)
Class (IMDG) : 8
Packing group (IMDG) : II
EmS Number : F-A, S-B
Marine Pollutant : No

Transport by sea

In accordance with IATA

UN-No. (IATA) : 2735
Proper Shipping Name (IATA) : Polyamines, liquid, corrosive, n.o.s. (1,5-Pentanediamine, 2-methyl-)
Class (IATA) : 8
Packing group (IATA) : II
Marine Pollutant : No

SECTION 15: Regulatory information

Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

Canada WHMIS Confidential Business Information (CBI): The HMIRA number issued for this CBI claim is #10411. The date of filing is 2016-09-23

International regulations

No additional information available

US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Isophorone diamine (2855-13-2)

U.S. - New Jersey - Right to Know Hazardous Substance List


1,3-Benzenedimethanamine (1477-55-0)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Date of issue : 06/01/2015
Revision date : 10/06/2016
Other information : None.

NFPA health hazard : 3
NFPA fire hazard : 1
NFPA reactivity : 0



PRO-SET® INF-210 Hardener

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

HMIS III Rating

Health : 3 Serious Hazard

Flammability : 1 Slight Hazard

Physical : 0 Minimal Hazard

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.



COMPOSITE
ENVISIONS